



Standard Features:

- Fully proportional drive and lift controls
- Unique combination of wide beams and large pins, in self-lubricating bearings, creates a larger load bearing surface in scissor pivot areas.
- The 400 lb. capacity roll-out, deck extension can be locked at increments or extended to full 48".
- Steering controller is mounted at the top of the joystick for easy one-handed operation.
- Adjustable mount allows
- Sheet loading entrance accommodates 48" wide material.
- Fold-down guardrail system.
- Hour meter.
- 110V power to platform.
- High torque power package.
- Ground controls at base.
- Dual automatic parking brake.
- Multi-axis tilt sensor.
- Powder coat finish.
- Multiple disc brakes.
- Manual brake release.
- Dual fuel power (gas and

- the controller to be positioned for maximum operator comfort.
- All mechanical and electrical components are easily accessible without raising the platform or swinging out trays.
- Components are logically grouped and wiring is numbered for easy reference.

- LP).
- Liquid cooled engine.
- Lifting lugs.
- U.S. patent #5,476,050.
- Canadian patent #2,115,870.
- Other patents pending.
- Absolute best value

Optional Features:

- Quad-Trax 4wd allows operators to conquer extreme terrain conditions.
- Auto-Leveling outriggers.
- Platform work lights.
- All motion alarm.
- Flashing beacon (continuous).
- Air line to platform.
- Automotive horn.
- 120V 2250W generator.
- Lanyard attachments (6).
- Platform swing gate.
- Removable upper control station.
- Additional LPG tank.
- Diesel engine.
- Non-marking RT tires.
- Foam filled tires.
- Turf tires.
- CSA compliant options.
- 1 year extended warranty.
- 2 year extended warranty.

Detailed Specs	3072RT		3772RT	
	U.S.	Metric	U.S.	Metric
Height:				
Working Height*	36 ft	11.14 m	43 ft	13.28 m
Platform Height	30 ft	9.14 m	37 ft	11.28 m
Max. Drive Height	30 ft	9.14 m	37 ft	11.28 m
Stowed Height (top guardrail)	108.5 in	2.75 m	106.75 in	2.63 m
Stowed Height (rails folded)	78.75 in	2.00 m	77 in	1.95 m
Guardrail Height	43.5 in	1.10 m	43.5 in	1.10 m
Toeboard Height	6.0 in	15 cm	6.0 in	15 cm
Ground Clearance	8.4 in	21.3 cm	8.4 in	21.3 cm
Dimensions:				
Length (stowed overall)	117.25 in	2.98 m	117.25 in	2.98 m
Width	72 in	1.83 m	72 in	1.83 m
Platform Length (extended)	158 in	4.01 m	158 in	4.01 m
Roll-out Deck Length	48 in	1.22 m	48 in	1.22 m
Wheelbase	86 in	2.18 m	86 in	2.18 m
Lift Capacity	1,000 lbs	454 kg	750 lbs	340 kg
Roll-out Deck capacity	400 lbs	181 kg	400 lbs	181 kg
Speeds:				
Raise/Lower Speed	26/28 sec	26/28 sec	32/38 sec	32/38 sec
Drive Speed (stowed)	4.0 mph	6.4 km/h	4.0 mph	6.4 km/h
Drive Speed (raised)	0.4 mph	0.6 km/h	0.4 mph	0.6 km/h
Performance:				
Gradeability	45%	45%	40%	40%

Turning Radius (inside)	73.25 in	1.86 m	73.25 in	1.86 m
Turning Radius (outside)	14 ft 2.5 in	4.33 m	14 ft 2.5 in	4.33 m
Weight (approx. **)	7,340 lbs	3329 kg	8,500 lbs	3856 kg
Brakes	Multiple disc brakes, dual rear wheel			
Power Source	Liquid cooled - gas/LP			
Controls	Proportional drive and lift controls			
Tires	26 X 12 D / 380 NHS			

*Metric equivalent of working height adds 2m to platform. U.S. adds 6 ft. to platform height.

**Weight may increase with certain options or configurations.

Meets requirements of ANSI A92.6-2006 & CSA B354.2-01.
Specifications subject to change without notice.

Brochures:

N. America/ANSI/CSA Spec (English, Paper Size: Letter)

[Download](#)

Operator Manual:

3072RT/3772RT ANSI Spec (English)

[Download](#)

These documents are distributed in PDF format and a reader, such as the freely downloadable Adobe Acrobat is required to view them. If you don't already have Acrobat installed, then click the link below to download the free viewer from Adobe, Inc.

