

PRODUCT SPECIFICATIONS FOR 236D3

Gross Power - SAE J1995	74.3 HP
Net Power - SAE 1349	73.2 HP
Displacement	203 in ³
Stroke	4.7 in
Bore	3.7 in
Net Flywheel Power	73.2 HP
Engine Model	Cat 3.3B DIT (turbo)
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
Net Power - ISO 9249	73.9 HP
Rated Operating Capacity	1800 lb
Tipping Load	3600 lb
Breakout Force - Tilt Cylinder	5003 lb
Rated Operating Capacity with Optional Counterweight	2000 lb
Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual

quick coupler (unless otherwise noted).

Operating Weight 6567 lb

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Wheel Base 43.5 in

Height - Top of Cab 82 in

Vehicle Width over Tires 66 in

Ground Clearance 7.7 in

Departure Angle 26°

Maximum Dump Angle 48°

Maximum Reach - With Arms Parallel to Ground 53.3 in

Turning Radius from Center - Machine Rear 64.5 in

Bucket Pin Height - Maximum Lift 122.9 in

Length - Without Bucket 108.9 in

BUCKET

**Rack Back Angle -
Maximum Height** 91°

**Turning Radius from
Center - Bucket** 83 in

**Turning Radius from
Center - Coupler** 51.8 in

**Clearance at
Maximum Lift and
Dump** 92.9 in

**Reach - Maximum
Lift/Dump** 16 in

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat 10 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

**Bumper Overhang -
Behind Rear Axle** 40.2 in

**Maximum Overall
Height** 156.6 in

**Length - With Bucket
on Ground** 137.3 in

**Bucket Pin Height -
Carry Position** 7.5 in

Hydraulic Flow - Standard - Loader Hydraulic Flow 20 gal/min

Hydraulic Flow - High Flow - Maximum Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - Standard - Hydraulic Power (Calculated)	39 HP
Hydraulic Flow - Standard - Loader Hydraulic Pressure	3335 psi
Hydraulic Flow - High Flow - Maximum Loader Hydraulic Flow	30 gal/min
Hydraulic Flow - High Flow - Hydraulic Power (Calculated)	58 HP
ROPS	ISO 3471:2008
FOPS	ISO 3449:2005 Level I
Travel Speed - Forward or Reverse - Two Speed Option	10.6 mile/h
Travel Speed - Forward or Reverse - One Speed	7 mile/h
Chain Box - Each Side	2.3 gal (US)
Cooling System	3.7 gal (US)
Engine Crankcase	3 gal (US)
Fuel Tank	24.8 gal (US)
Hydraulic System	13.2 gal (US)
Hydraulic Tank	10.3 gal (US)
Outside Cab**	101 dB(A)

Note (2) *The declared dynamic operator sound pressure levels per ISO 6396:2008. The

measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Note (3)

**The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Inside Cab*

83 dB(A)

Note (1)

Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

**Air
Conditioning**

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.81 kg of refrigerant which has a CO2 equivalent of 1.158 metric tonnes.

236D3 STANDARD EQUIPMENT

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Adjustable Front and Rear Halogen Lights, Dome Light
Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control

Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Parking Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S·O·SSM Sampling Valve, Hydraulic Oil

Filters, Cartridge-type, Hydraulic

Filters, Canister-type, Fuel and Water Separator

Radiator/Hydraulic Oil Cooler (side-by-side)

Spring Applied, Hydraulically Released Parking Brakes

Hydrostatic Transmission

Four Wheel Chain Drive

OTHER

Engine Enclosure, Lockable

Extended Life Antifreeze, -36° C (-33° F)

Machine Tie Down Points (6)

Support, Lift Arm

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge

Radiator, Expansion Bottle

Cat ToughGuard™ Hose

Auxiliary, Hydraulics, Continuous Flow

Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release

Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm

Electrical Outlet, Beacon

Belly Pan Cleanout

Variable Speed Demand Fan

Product Link™ PL240, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow

Quick Coupler, Mechanical or Powered

Highly Visible Seat Belt, 50 mm (2 in) or 75 mm (3 in)

EU Preparation Package

Power Train: One Speed, One Speed with Speed Sensitive Ride Control, Two Speed or Two Speed with Speed Sensitive Ride Control

Tires, 10 × 16.5 or 12 × 16.5

PERFORMANCE PACKAGES:

- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

COMFORT PACKAGES:

- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

236D3 OPTIONAL EQUIPMENT

OPTIONAL EQUIPMENT

Hand-Foot Style Controls

External Counterweights

Beacon, Rotating

Engine Block Heater - 120V

Oil, Hydraulic, Cold Operation

Paint, Custom

Product Link PL641, Cellular

Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)

