

PRODUCT SPECIFICATIONS FOR 262D3

Gross Power - SAE J1995	74.3 HP
Net Power - SAE 1349	72.9 HP
Displacement	203 in ³
Stroke	4.7 in
Bore	3.7 in
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
Net Power - ISO 9249	73.7 HP
Engine Model	Cat C3.3B DIT (turbo)
Net Flywheel Power	72.9 HP
Rated Operating Capacity	2700 lb
Rated Operating Capacity with Optional Counterweight	3055 lb
Tipping Load	5400 lb
Breakout Force - Tilt Cylinder	7355 lb
Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual

quick coupler (unless otherwise noted).

Operating Weight 8296 lb

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Wheel Base 49.2 in

Length - With Bucket on Ground 146.2 in

Length - Without Bucket 117.9 in

Height - Top of Cab 83.1 in

Vehicle Width over Tires 66 in

Maximum Overall Height 157.8 in

Bucket Pin Height - Maximum Lift 124.9 in

Bucket Pin Height - Carry Position 7.9 in

Reach - Maximum Lift/Dump 30.9 in

Clearance at Maximum Lift and 93.7 in

Maximum Lift and Dump**Ground Clearance** 8.9 in**Departure Angle** 26°**Bumper Overhang - Rear Axle** 42.6 in**Maximum Dump Angle** 51°**Rack Back Angle - Maximum Height** 84°**Bucket Pin Reach - Maximum Lift** 15.5 in**Turning Radius from Center - Bucket** 85.9 in**Turning Radius from Center - Coupler** 55.2 in

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, one speed, OROPS, 1730 mm (68 in) low profile bucket, Cat PC 12 × 16.5 tires, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Maximum Reach - With Arms Parallel to Ground 50.9 in**Turning Radius from Center - Machine Rear** 71.1 in**Hydraulic Flow - High Flow Mode - Maximum Loader Hydraulic Pressure** 4061 psi

Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Pressure	4001 psi
Hydraulic Flow - High Flow XPS - Hydraulic Power (Calculated)	76 HP
Hydraulic Flow - Standard - Hydraulic Power (Calculated)	44 HP
Hydraulic Flow - Standard - Loader Hydraulic Pressure	3335 psi
Hydraulic Flow - Standard - Loader Hydraulic Flow	23 gal/min
Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Flow	32 gal/min
ROPS	ISO 3471:2008
FOPS	ISO 3449:2005 Level I
Travel Speed - Forward or Reverse - Two Speed Option	11 mile/h
Travel Speed - Forward or Reverse - One Speed	7.7 mile/h
Chain Box - Each Side	3.3 gal (US)
Cooling System	3.7 gal (US)
Engine Crankcase	3 gal (US)
Fuel Tank	27.7 gal (US)
Hydraulic System	13.7 gal (US)
Hydraulic Tank	10.3 gal (US)

Note (1) Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

Inside Cab* 81 dB(A)

Note (2) *The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Outside Cab** 101 dB(A)

Note (3) **The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Air Conditioning The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO2 equivalent of 1.430 metric tonnes.

262D3 STANDARD EQUIPMENT

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Rear Halogen Working Lights, Two Adjustable Front Halogen Lights, Dome Light

Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control
Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Park Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S·O·SSM Sampling Valve, Hydraulic Oil

Filters, Cartridge-type, Hydraulic
Filters, Canister-type, Fuel and Water Separator
Radiator/Hydraulic Oil Cooler (side-by-side)
Spring Applied, Hydraulically Released Parking Brakes
Hydrostatic Transmission
Four Wheel Chain Drive

OTHER

Engine Enclosure, Lockable
Extended Life Antifreeze, -37° C (-34° F)
Machine Tie Down Points (6)
Support, Lift Arm
Hydraulic Oil Level Sight Gauge
Radiator Coolant Level Sight Gauge
Radiator, Expansion Bottle
Cat ToughGuard™ Hose
Auxiliary, Hydraulics, Continuous Flow
Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release
Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm
Electrical Outlet, Beacon
Belly Pan Cleanout
Variable Speed Demand Fan
Product Link™ PL240, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow XPS
Quick Coupler, Mechanical or Powered
High Visibility Seat Belt, 50 mm (2 in) or 75 mm (3 in)
Power Train: One Speed, One Speed with Ride Control, Two Speed or Two Speed with Ride Control

PERFORMANCE PACKAGES:

- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow XPS, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

COMFORT PACKAGES:

- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

262D3 OPTIONAL EQUIPMENT

OPTIONAL EQUIPMENT

Hand-Foot Style Controls

External Counterweights

Beacon, Rotating

Engine Block Heater – 120V

Oil, Hydraulic, Cold Operation

Paint, Custom

Heavy Duty Battery, 1,000 CCA

Product Link PL641, Cellular

Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)

